

| Steps                             | TASKI Products   | TASKI Pads & Brushes                              |
|-----------------------------------|--|---|
| Initial Cleaning (Step 1)         | TASKI Profi  | Purple Pad  |
| Finishing (Step 2)                | TASKI Vision Matte - Satin Gloss<br>TASKI Vision Star - High Gloss | Rayon mop or lamb's wool                          |
| Neutral Cleaner (Step 3)          | TASKI R50<br>TASKI Wiwax   | TASKI Contact pad, purple pad or soft nylon brush |
| Heavy Soil Cleaner<br>(Step 4, 6) | TASKI Profi  | TASKI Contact pad, purple pad or soft nylon brush |
| Stripping (Step 5)                | TASKI Ice it   | Black pad   |
| Restorer (Step 3, 4)              | TASKI Wiwax  | TASKI Contact pad, purple pad or soft nylon brush |

## **EQUIPMENT NEEDED**

- Broom
- Wet Mop
- Wet/Dry Vacuum
- Auto Scrubber
- Buffer

## STEP 1: INITIAL CLEANING

- A. Sweep and dry vacuum to ensure fine soil is removed.
- B. Wet scrub with TASKI Profi cleaner (6-8 oz/gal of water). Using buffer or auto scrubber with TASKI contact pad or soft nylon brush.
- C. Wet Vacuum remaining soiled solution, rinse (1-2 times) and allow to dry thoroughly (8-8 hours).

## **STEP 2: FINISHING**

- A. TASKI Vision Matte for low satin finish Apply 4 thin coats of finish allowing a aminimum of 30 minutes dry time or until thoroughly dry between coats.
- B. Provide sufficient cure time of final coat before allowing foot traffic (at least 2 hours).