

playfall®

Safety Surfacing System

1 – GENERAL

1.01 GENERAL

Recycled PlayFALL rubber safety surfacing tiles are manufactured using SBR rubber granules and buffings with either color pigments or EPDM color granules. Colors to be selected from GSP standard colors. Custom colors are available on request.

- Installation must follow manufacturer's standard Installation Procedures. PlayFALL safety tiles are covered by a limited 5 year manufacturer's warranty.
- PlayFALL safety tiles are manufactured to comply with ASTM-1292-04 attenuation standards and exceed ADA requirements

2 – MATERIAL

2.01 MATERIAL

PlayFALL rubber safety tiles are made from recycled SBR "truck" tire rubber buffings and granules. (Truck tires are used rather than car tires because of the superior grade of rubber.) The tiles are made in a dual layer format with the upper finish layer having a higher density for stability, and the lower layer including stanchions at a reduced density for optimum impact attenuation. Standard Colors are produced by using a pigment additive mixed with the non-toxic polyurethane binder. EPDM color rubber granule finishes are also available for top layer.

- PlayFALL rubber safety tiles are 24" x 24" and are available in five thicknesses: 45mm (1.75") , 65mm (2.5") , 75mm (3") , & 85mm (3.25") , 107mm (4.25")
- Interlock pins for placing into preset holes for surface security and integrity: PVC dowels 15mm (5/8") round x 75mm (3") long

2.02 ACCESSORIES AVAILABLE

- A. Beveled Edge Ramps for transition from top of tile to grade.

2.03 TECHNICAL DATA

Test:	Description:	Tile:	Result:	
ASTM-1292-04	Impact Attenuation		Basic	EPDM
		45mm	4' fall ht.	3' fall ht.
		65mm	6' fall ht.	5' fall ht.
		75mm	8' fall ht.	6' fall ht.
		85mm	9' fall ht.	8' fall ht.
		107mm	10' fall ht.	9' fall ht.

3 – INSPECTION REQUIREMENTS

3.01 INSPECTION REQUIREMENTS

A thorough inspection of PlayFALL safety tiles and all accessories must be done on site upon delivery, to ensure proper quantity and integrity of materials.

- A thorough review of site conditions must be performed to ensure structural integrity and proper completion of any and all site preparation.
- Refer to complete PlayFALL Installation Manual specifications and procedures, as prepared by GSP, for preparation and installation detail.

3.02 INSTALLATION REQUIREMENTS

Proper Installation methods and procedures must be followed as outlined in the PlayFALL Installation Manual prepared by GSP.

Proper Installation methods and procedures must be followed as outlined in the PlayFALL Installation Manual prepared by GSP.

4 – WARRANTY

4.01 5 YEAR LIMITED WARRANTY

Subject to the following terms and conditions, GSP hereby warrants to the Original Purchaser that the PlayFALL Safety Surface Tiles will be free from manufacturing defects for a period of 5 years.

4.02 WARRANTY COVERAGE

- A. GSP warrants that the PlayFALL Safety Surfacing Tiles have been tested and comply with ASTM F1292-04 Fall Height Performance Specifications.
- B. GSP warrants that the PlayFALL Safety Surfacing Tiles will maintain their fall height performance for a period of five years from date of purchase.
- C. Top layer finish surface will not wear greater than 1/4" per year when used under normal conditions.

4.03 WARRANTY DURATION

- A. This Warranty will commence at the date the product has been delivered to the job site.
- B. The Warranty will continue for 5 years from the date of delivery to the job site, as documented by an invoice or bill of lading with the Original Purchaser.

4.04 WARRANTY REMEDIES

- A. GSP warrants each tile to be free from defects in material or workmanship and agrees to replace tiles (product only) which disclose such defects when used under normal conditions.
- B. GSP will not accept responsibility under the warranty for anything more than replacement of the product, FOB Abbotsford, BC., Canada. In the event of a Warranty Claim, contact your dealer.
- C. This remedy is the sole and exclusive remedy available to the Original Purchaser for breach of express or implied representations or warranties with respect to the product.

4.05 WARRANTY EXCLUSIONS

- A. This warranty is in lieu of all other representations, warranties, guarantees, obligations or liability, expressed or implied, including any warranty of merchantability or fitness for a particular purpose other than playground covering.

The product will not be covered under warranty if/when:

- i. A natural disaster occurs, including, but not limited to, flooding, earthquakes, tornadoes, hurricanes, etc.
 - ii. An act of negligence, abuse, accident, misuse, including but not limited to, vandalism, civil disobedience, act of crime, act of war and the like occurs.
 - iii. Acids, caustic materials or petroleum chemicals and the like, direct or airborne, are or have been in contact with the product.
- B. Improper installation or maintenance of the product, including, but not limited to, the product being found to have been installed on top of foreign material such as loose sand, bark, dust, etc.

In no event will GSP be liable to the Original Purchaser or any third party for any damages, including any lost profits, lost savings or other consequential or incidental damages arising out of the use or inability to use the product even if GSP and/or its representatives have been advised of the possibility of these damages. The liability of GSP for damages resulting from the use or misuse of the product shall in no event exceed the replacement cost of the product, FOB Abbotsford, BC, Canada.

In the event of a Warranty Claim, Proof of Purchase from GSP or a qualified dealer is necessary for the Warranty to be valid. Some jurisdictions do not allow the limitation of liability for incidental or consequential damages so the above limitation or exclusion may not apply.