

playfall®

Safety Surfacing System

Care & Maintenance Instructions

CLEANING & MAINTENANCE

- All excess adhesive should be cleaned off tiles immediately using a damp cloth.
- If adhesive has dried onto tile surface, scrape off with utility knife and rub with cloth containing mineral spirits.
- A regular routine maintenance program will enhance the appearance and performance of PlayFALL tiles.
- Tile surfaces can be swept, vacuumed, machine scrubbed, hosed-off or power sprayed to ensure a clean and long lasting safety surface.
- Please note that PlayFALL tiles will allow liquids to pass through them, so site drainage is mandatory for tile performance. In indoor installations, odor and bacteria may develop if liquids seep into tiles. All spills and excess liquids should be removed/extracted immediately to ensure a clean and sanitary site.

DISCLAIMER

This manual has been prepared to assist purchasers of PlayFALL Safety Tiles in the recommended installation procedure. It is a guideline which may be used to produce an effective finished installation and should be reviewed in the context of the installation site(s).

GSP, does not warrant any installation work not directly performed by GSP, and specifically disclaims liability for any direct or indirect personal injury, property damage or other costs or losses resulting from installations or applications by third parties. Please see the GSP, Limited Warranty for the particulars of warranty coverage relating to GSP, products.

- PlayFALL is not to be used for any purpose other than playground covering.
- PlayFALL must only be used in accordance with the manufacturer's published specifications.
- PlayFALL is not to be used for any purpose other than playground covering.
- PlayFALL must only be used in accordance with the manufacturer's published specifications.